



Ürün Hakkında

Aksa power generation system, providing optimum performance, and reliability, for stationary standby, prime power, and continuous duty applications. All generator sets are factory build, and production tested.

Güç

3 Phase, 60 Hz, PF 0.8

Voltaj (V)	STANDBY GÜÇ(ESP)		PRIME GÜÇ (PRP)		STANDBY AKIM (A)
	kW	kVA	kW	kVA	
380 / 220	88,0	110	80.00	100	167
480 / 277	100,0	125	92.00	115	150
208 / 120	96,0	120	88.00	110	333

STANDBY RATING (ESP) Güvenilir bir şebeke kaynağının güç kesintisi süresince değişken elektrik yüküne güç sağlamak için geçerlidir. ESP, ISO 8528-1'e uygundur. Aşırı yüklemeye izin verilmez.

PRIME RATING (PRP) Değişken elektrik yüküne sınırsız saat boyunca güç sağlamak için geçerlidir. PRP, ISO 8528-1'e uygundur. %10 aşırı yük kapasitesi, 12 saatlik çalışma süresi içinde 1 saatlik bir süre için kullanılabilir.

Genel Özellikler

Model Adı	AP 125-6
Frekans (Hz)	60
Yakıt Tipi	Diesel
Motor Marka ve Modeli	Perkins 1104C-44TAG2
Alternatör Marka ve Modeli	Mecc Alte ECP 34-2S/4 C
Kontrol Panel Modeli	DSE 6020
Kabin Modeli	AK 40

Motor Özellikleri

Genel Bilgiler

Üretici	Perkins
Motor Modeli	1104C-44TAG2
Silindir Sayısı / Tipi	4 cylinders - in line



Bore mm (in)	105
Stroke mm (in)	127
Hacim l (cu. In)	4.4
Sıkıştırma Oranı	18.23:1
Motor Hızı (rpm)	1800
Standby Güç (kW/hp)	117.5/157.57
Prime Güç (kW/hp)	106.8/143.22
Blok Isıtıcı (Adt)	1
Blok Isıtıcı Gücü (Watt)	750
Governor Sistemi	Perkins LCS electronic
Hava Filtresi	Dry Type
Hava Emiş	Turbo Charged and Intercooled (Air to Air)

Yağlama Sistemi

Yağ Kapasitesi l (gal)	8
Maks. Yağ Sıcaklığı °C (F)	125

Yakıt Sistemi

Yakıt Tipi	Diesel
Enjeksiyon Tipi	Direct
Yakıt Pompa Tipi	Rotary

Elektrik Sistemi

Çalışma Voltajı (Vdc)	12 Vdc
Akü ve Kapasite (Adt/Ah)	1x66
Şarj Alternatörü (A)	65

Soğutma Sistemi

Soğutma Metodu	Water Cooled
Soğutma Suyu Kapasitesi (yalnızca motor)l (gal)	7

Egzoz Sistemi

Egzoz Gaz Debisi (m³/dk)	20.4
Egzoz Geri Basınç in-Hg (kPa)	15
Egzoz Gaz Sıcaklığı °C (F)	574
Egzoz Geçen Isı kW (BTU/min)	99.7

Radyatör

Toplam Soğutma Suyu Kapasitesi (l)	12.6
Soğutma Fan Hava Debisi m³/min (ft³/min)	225.6



Soğutma Havası Harici Direnç (Pa)	125
-----------------------------------	-----

Yakıt Tüketimi

%100 Prime Yükte Yakıt Tüketimi l/h (kg/h)	26.9
%75 Prime Yükte Yakıt Tüketimi l/h (kg/h)	20.2
%50 Prime Yükte Yakıt Tüketimi l/h (kg/h)	14.1

Alternator Özellikleri

Üretici	Mecc Alte
Alternatör Model	ECP 34-2S/4 C
Frekans (Hz)	60
Güç (kVA)	120
Voltaj (V)	480
Faz	3
A.V.R.	DSR
Voltaj Regülasyon	1
Yalıtım Sınıfı	H
Koruma Sınıfı	IP23
Nominal Güç Faktörü	0.8
Toplam Generator Ağırlık (kg)	349
Sıcaklık Artış Sınıfı	H
Soğutma Havası (m³/dk)	34.4

Açık Jeneratör Boyutları

Uzunluk mm	2150
Genişlik mm	1050
Yükseklik mm	1490
Açık Gen.Set Brüt Ağırlık, Kuru kg	1120
Yakıt Tank Kapasitesi (l)	240

Kabin Özellikleri

Uzunluk mm	3105
Genişlik mm	1107
Yükseklik mm	1803
Kuru Ağırlık kg	1470
Yakıt Tank Kapasitesi (l)	240

Kontrol Paneli



Üretici	DSE
Kontrol Modül Modeli	DSE 6020
İletişim Portları	N/A



1. Main status display.
2. Display scroll button.
3. Page(information) button.
4. Common alarm indicator.
5. Status LED's.
6. Operation selecting buttons.

Standart Cihazlar

- DSE, model 6020 Auto Mains Failure control module.
- Battery charger input 198-264 volt, output 27,6 V 5 A (24 V) or 13,8 Volt 5A (12V)
- Emergency stop push button and fuses for control circuits.

Kontrol Ünitesi

The DSE 6020 is a standard control module for our generator sets up to 200kVA and it has been designed to start and stop diesel and gas generator sets.

The DSE 6020 module has been designed to monitor generator frequency, volt, current, engine oil pressure, coolant temperature running hours and battery volts.

Module monitors the mains supply and switches over to the generator when the mains power fails.

The DSE6020 also indicates operational status and fault conditions, Automatically shutting down the Gen. Set and giving true first-up fault condition of Gen. Set failure. The LCD display indicates the fault.

Yapım ve Boya

- Components installed in a sheet steel enclosure. Phosphate chemical, pre-coating of steel provides corrosion resistant surface. Polyester composite powder topcoat forms a high gloss and extremely durable finish. Lockable and hinged panel door provides easy access to components.

Montaj

Control panel is mounted on baseframe with steel stand. Located at the right side of the generator set (When you look at the Gen.Set. from Alternator)

Opsiyonlar

Kontrol Paneli Uyumluluk Listesi



- Flexible sensor can be controlled with temperature, pressure, percentage (warning/shutdown/electrical trip)
- Local setting parameters and monitoring from PC to control module with USB connection (max 6 mt).

- Electrical Safety / EMC compatibility
- BS EN 60950 Electrical business equipment.
 - BS EN 61000-6-2 EMC immunity standard.
 - BS EN 61000-6-4 EMC emission standard

Statik Akü Şarj Cihazı

- Battery charger is manufactured with switching-mode and SMD technology and it has high efficiency. Battery charger models' output V-I characteristic is very close to square and output is 5 amper, 13,8 V for 12 volt and 27,6 V for 24 V . Input 198 - 264 volt AC. Proline 2405 has fully output short circuit protection and it can be used as a current source. Proline 1205/2405 charger has high efficiency, long life, low failure rate, lightweight and low heat radiated in accordance with linear alternatives. The charger is fitted with a protection diode across the output. Connect charge fail relay coil between the positive output and CF output. They are equipped with RFI filter to reduce electrical noise radiated from the device. Galvanically isolated input and output typically 4kV for high reliability.

Standart Ekipmanlar

- Water cooled, Diesel engine
- Radiator with mechanical fan
- Protective grille for rotating and hot parts
- Electric starter and charge alternator
- Starting battery (with lead acid) including rack and cables
- Engine coolant heater
- Base frame design incorporates an integral fuel tank and anti-vibration isolators
- Flexible fuel connection hoses
- Single bearing, class H alternator
- Industrial exhaust silencer and steel bellows supplied separately(for open sets)
- Static battery charger
- Manual for application and installation

Opsiyonel Ekipmanlar

Motor

- Fuel-Water Separator Filter
- Oil heater

Alternatör

- Anti-Condensation Heater
- Over sized alternator
- PMG excitation + AVR
- Main line circuit breaker

Kontrol Paneli

- Automatic synchronising and power control system (Multi gen-set Parallel)
- Parallel system with mains
- Transition synchronization with mains
- Alarm output relays
- Earth fault, single set

Transfer Panosu

- Three or four pole contactor
- Three or four pole motor operated circuit breaker



- Parallel system with mains
- Remote relay output
- Remote communication with modem
- Charge Ammeter

Yardımcı Ekipmanlar

- Main Fuel Tank
- Automatic or manual fuel filling system
- Electrical or manual oil drain pump
- Low and high fuel level alarm
- Inlet and outlet motorized louvers
- Inlet and outlet acoustic baffles
- Tool kit for maintenance
- 1500/3000 hours maintenance kit
- Supplied with oil and coolant (-30°C)

Kabin

- Galvanized Coating
- ISO Container
- Marine Grade Paint

Egzoz

- Residential Silencer
- Silencer Spark Arrester
- Critical Silencer
- Catalytic Converter

Opsiyonel Alternatör ve Kontrol Paneli

Please contact to your reseller for additional Alternator, Control Panel and Breaker Switch options.

Aksa Sertifikalar**Direktifler**

- 2006/42/EC : Machinery Safety Directive
- 2014/30/EU : Electromagnetic Compatibility Directive
- 2014/35/EU : Low Voltage Directive

Standartlar

- TS ISO 8528-5:2022 / TS EN ISO 8528-13:2018 : Reciprocating internal combustion engine-driven alternating current generating sets- Part:13: Safety

Quality Management Systems

ISO 9001:2015
ISO 14001:2015
ISO 45001:2018
ISO 50001:2018
ISO 27001:2013
ISO 10002:2018